



# TECHNICAL SPECIFICATIONS

## Performance

<b>IEPE/Charge Selection</b>	Individual channel selection, two-way switch
<b>IEPE Channel Indicator</b>	LED Warning (Green: OK; Red: Short Circuit; Off: Open Circuit)
<b>Input Gain Options (per channel)</b>	x1, x10 and x100
<b>No. of Channels</b>	3
<b>Output Dynamic Range</b>	±10V AC
<b>Output Dynamic Range</b>	
<b>Frequency Response (±5%)</b>	
<b>Frequency Response (±10%)</b>	
<b>Bandwidth</b>	
<b>Phase Response (0° ±1%)</b>	
<b>Phase Response (0° ±4%)</b>	
<b>Linearity</b>	

## Connections

<b>Inputs</b>	3x BNC jacks
<b>Outputs</b>	3x BNC jacks
<b>Environmental</b>	≤1%
<b>Operating Temperature (Stated Performance Limits)</b>	20°C ±5°C (20°C ±5°C)
<b>Operating Temperature</b>	32 to 113°F
<b>Storage Temperature</b>	

## Power

<b>Input Connector</b>	2.1mm DC Socket
<b>Input Voltage Range</b>	9 – 30 VDC (nom.18VDC)
<b>Status</b>	Green LED Power Indicator on Front Panel
<b>Maximum Power Rating</b>	5W
<b>Fuse Rating</b>	24VDC/4mA

## Physical

<b>Weight</b>	0.59kg
<b>Size (metric)</b>	124 x 46 x 195mm
<b>(imperial)</b>	4.88 x 1.81 x 7.67"

DJB INSTRUMENTS UK LIMITED

e: sales@djbinstruments.com

t: +44 (0) 1638 712288

w: djbinstruments.com



ISO 9001 – 00025363



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

ALL DEVICES CALIBRATED IN ACCORDANCE WITH BS ISO 16063-21:2003. ALL DEVICE CALIBRATIONS ARE UKAS TRACEABLE.