

VC/01

Hand-held calibrator



TECHNICAL SPECIFICATIONS

Performance

Acceleration (±3%)	1g (9.81 m/s ²) RMS
Velocity (±3%)	9.81mm/s ² RMS
Displacement (3%)	9.81µm RMS
Vibration Frequency ±1%	159.2Hz
Output Waveform	Sine
Waveform Distortion	≤3%
Maximum Load	100 grams
Size	Ø52x155mm
Weight	600 grams (with batteries)
Working Temperature	0 to +55°C (32 to 131°F)
Storage Temperature	-45 to +85°C (-49 to 185°F)
Battery Power Supply	1x PP3 (9V DC) *
Automatic Shutdown	After 50 seconds
Material	Aluminium, black painted
LED Power Indicators	Normal: Green, Low Battery: Orange

* = batteries are not included with device.

DJB INSTRUMENTS UK LIMITED

e: sales@djbstruments.com

t: +44 (0) 1638 712288

w: djbstruments.com



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

ALL DEVICES CALIBRATED IN ACCORDANCE WITH BS ISO 16063-21:2003. ALL DEVICE CALIBRATIONS ARE UKAS TRACEABLE.