



IH/10

Impact Hammer

0.5mV/N Sensitivity, BNC Connector, 10000N pk Measurement Range

TECHNICAL SPECIFICATIONS

Performance

| | |
|--|---------------------|
| Sensitivity ($\pm 10\%$) | 0.5mV/N |
| Measurement Range | 10000N pk |
| Non-linearity (% FS) | $\leq 1\%$ |
| Resolution | 250mN rms |
| Resonant Frequency | $\geq 45\text{kHz}$ |
| Low Frequency | 0.5Hz |


Electrical Characteristics

| | |
|-------------------------|------------------|
| Supply Voltage | 18 to 28V DC |
| Supply Current | 2 to 10mA |
| Bias Voltage | 10 to 14V DC |
| Output Impedance | $\leq 100\Omega$ |

Physical

| | |
|------------------------------|-------|
| Head Weight | 445g |
| Head Diameter | 32mm |
| Hammer Length | 350mm |
| Hammer Weight (total) | 0.9kg |
| Connector | BNC |

DIMENSIONS



All measurements in millimeters (mm)
Not to scale

INCLUDED WITH DEVICE

- ✓ 3 interchangeable tips

Soft Medium Hard



- ✓ 2 metre BNC to BNC cable
- ✓ Other cable options and lengths available

DEVICE OPTIONS

| | |
|----------|--|
| IH/01 | 25mV/N Sensitivity, BNC Connector, 200N pk Measurement Range |
| IH/01-50 | 100mV/N Sensitivity, M5 Connector, 50N pk Measurement Range |
| IH/02 | 2.5mV/N Sensitivity, BNC Connector, 2kN pk Measurement Range |
| IH/05 | 1mV/N Sensitivity, BNC Connector, 5kN pk Measurement Range |
| IH/10 | 0.5mV/N Sensitivity, BNC Connector, 10kN pk Measurement Range |
| IH/20 | 0.25mV/N Sensitivity, BNC Connector, 20kN pk Measurement Range |
| IH/50 | 0.1mV/N Sensitivity, BNC Connector, 50kN pk Measurement Range |

DJB INSTRUMENTS UK LIMITED

e: sales@djbinstruments.com

t: +44 (0) 1638 712288

w: djbinstruments.com



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

ALL DEVICES CALIBRATED IN ACCORDANCE WITH BS ISO 16063-21:2003. ALL DEVICE CALIBRATIONS ARE UKAS TRACEABLE.