



# Petrowax

## TECHNICAL SPECIFICATIONS

### Physical

<b>Size</b>	25 x 25mm box
<b>Colour</b>	Purple

### Environmental

<b>Flash Point</b>	>93.4°C (200°F) - Method: PMCC, ASTM D93
<b>Density</b>	>0.80 g/cm <sup>3</sup> at 20°C
<b>Solubility in Water</b>	Insoluble
<b>Kinematic viscosity</b>	13 – 18 mm <sup>2</sup> /s at 100°C
<b>Boiling Point</b>	> 230°C
<b>Specific gravity (H<sub>2</sub>O=1)</b>	<1
<b>Partitioning coefficient</b>	log POW: >6 This product is soluble in oil.
<b>Melting Point</b>	54 – 102°C unless specified below

Do not handle at temperatures >+90°C.

Store in a dry place. Keep container tightly closed. Keep out of strong sunlight. Do not store at temperatures: >+90°C.

DJB INSTRUMENTS UK LIMITED

e: sales@djbinstruments.com

t: +44 (0) 1638 712288

w: djbinstruments.com



SPECIFICATIONS MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

ALL DEVICES CALIBRATED IN ACCORDANCE WITH BS ISO 16063-21:2003. ALL DEVICE CALIBRATIONS ARE UKAS TRACEABLE.